


Notes:


1. All locating is to be done from the two tooling holes.  
(Note that the tooling holes on the Top Cover line up with the tooling holes on the Probe Plate)
2. Take care to drill from the top side of the Top Cover.  
The spring holes are closest to the top of the Top Cover.



Top View  
Spring holes are closest to top side  
(See Note 2)

FINISH	MATERIAL	DEFAULT DIMENSIONS	REVISION HISTORY					<b>Automatiq</b>		<b>Measurement Systems</b>		552 Acton Road Columbus OH 43214		
Leave protective cover on  Protect from scratches  Break sharp corners	0.500" Thick Clear Polycarbonate Sheet  0.125" x 0.875" Stainless Steel Dowel Pin (Two)	INCHES	REV	ECO	CHANGE	DATE	BY							
		DEFAULT TOLERANCES	A	-	Original Drawing	21 Jun 2018	BuB							
			B	-	Update Formatting	03 Jan 2021	BuB							
		0.000 ±0.010	A											
		0.00 ±0.025	B											
		0.0 ±0.050	C											
			D											
Versi-Traq Test Fixture							Design Study							
FMP00028.02							Top Cover – Standard							
DWG-00431							REV	B-1	SHEET	1/6	SIZE	B	SCALE	1:2
Copyright © 2021 Automatiq Measurement Systems LLC. All Rights Reserved. <b>CONFIDENTIAL</b>														

- Notes:
1. All locating is to be done from the two tooling holes.  
  
(Note that the tooling holes on the Top Cover line up with the tooling holes on the Probe Plate)
  2. Take care to drill from the top side of the Top Cover.  
The spring holes are closest to the top of the Top Cover.



Top View  
Spring holes are closest to top side  
(See Note 2)

FINISH	MATERIAL	DEFAULT DIMENSIONS	REVISION HISTORY						<div>Automatiq</div> <div>Measurement Systems</div> <div>552 Acton Road Columbus OH 43214</div>								
Leave protective cover on  Protect from scratches  Break sharp corners	0.500" Thick Clear Polycarbonate Sheet  0.125" x 0.875" Stainless Steel Dowel Pin (Two)	INCHES	REV	ECO	CHANGE	DATE	BY	Versi-Traq Test Fixture			Design Study						
		DEFAULT TOLERANCES	A		Original Drawing	21 Jun 2018	BJB										
			B		Update Formatting	03 Jan 2021	BJB	FMP00028.02		Top Cover – Wide							
			C									DWG-00431		REV B-1		SHEET 2/6	
			D														
	E																
	F																
	G																
	H																

Copyright © 2021 Automatiq Measurement Systems LLC. All Rights Reserved. **CONFIDENTIAL**

Notes:

1. All locating is to be done from the two tooling holes.  
(Note that the tooling holes on the Top Cover line up with the tooling holes on the Probe Plate)
2. Take care to drill from the top side of the Top Cover.  
The spring holes are closest to the top of the Top Cover.




Top View  
Spring holes are closest to top side  
(See Note 2)

FINISH	MATERIAL	DEFAULT DIMENSIONS	REVISION HISTORY					<b>Automatic</b> Measurement Systems		552 Acton Road Columbus OH 43214			
Leave protective cover on	0.500" Thick Clear Polycarbonate Sheet	INCHES	REV	ECO	CHANGE	DATE	BY						
Protect from scratches		DEFAULT TOLERANCES	A	-	Original Drawing	21 Jun 2018	BJB						
Break sharp corners		0.125" x 0.875" Stainless Steel Dowel Pin (Two)	0.000 ±0.010	B	-	Update Formatting	03 Jan 2021	BJB					
			0.00 ±0.025	A									
			0.0 ±0.050	B									
			C										
			D										
			E										
			F										
			G										
			H										
								Versi-Traq Test Fixture		Design Study			
								FMP00028.02		Top Cover – Extra Wide			
								DWG-00431		REV B-1	SHEET 3/6	SIZE B	SCALE 1:2
Copyright © 2021 Automatic Measurement Systems LLC. All Rights Reserved. <b>CONFIDENTIAL</b>													

Notes:


1. All locating is to be done from the two tooling holes.  
(Note that the tooling holes on the Top Cover line up with the tooling holes on the Probe Plate)
2. Take care to drill from the top side of the Top Cover.  
The spring holes are closest to the top of the Top Cover.



Top View  
Spring holes are closest to top side  
(See Note 2)

FINISH	MATERIAL	DEFAULT DIMENSIONS	REVISION HISTORY				Automatiq	Measurement Systems		552 Acton Road Columbus OH 43214		
Leave protective cover on  Protect from scratches  Break sharp corners	0.500" Thick Clear Polycarbonate Sheet  0.125" x 0.875" Stainless Steel Dowel Pin (Two)	INCHES	REV	ECO	CHANGE	DATE						BY
		DEFAULT TOLERANCES	A	-	Original Drawing	21 Jun 2018	BuB					
			B	-	Update Formatting	03 Jan 2021	BuB					
		0.000 ±0.010	A									
		0.00 ±0.025	B									
		0.0 ±0.050	C									
							Versi-Traq Test Fixture			Design Study		
							FMP00028.02		Top Cover – Deep			
							DWG-00431		REV B-1	SHEET 4/6	SIZE B	SCALE 1:2
Copyright © 2021 Automatiq Measurement Systems LLC. All Rights Reserved. <b>CONFIDENTIAL</b>												

- Notes:
- All locating is to be done from the two tooling holes.  
  
(Note that the tooling holes on the Top Cover line up with the tooling holes on the Probe Plate)
  - Take care to drill from the top side of the Top Cover.  
The spring holes are closest to the top of the Top Cover.



Top View  
Spring holes are closest to top side  
(See Note 2)

FINISH	MATERIAL	DEFAULT DIMENSIONS	REVISION HISTORY				Automatiq Measurement Systems			
Leave protective cover on Protect from scratches Break sharp corners	0.500" Thick Clear Polycarbonate Sheet  0.125" x 0.875" Stainless Steel Dowel Pin (Two)	INCHES	REV	ECO	CHANGE	DATE	BY	Versi-Traq Test Fixture		
		DEFAULT TOLERANCES	A	-	Original Drawing	21 Jun 2018	BJB	Design Study		
			B	-	Update Formatting	03 Jan 2021	BJB	FMP00028.02		
			C	-				Top Cover – Deep and Wide		
		0.000 ±0.010	D	-				DWG-00431		
		0.00 ±0.025	E	-				REV	B-1	SHEET
		0.0 ±0.050	F	-				5/6	SIZE	B
			G	-				SCALE	1:2	
			H	-				Copyright © 2021 Automatiq Measurement Systems LLC, All Rights Reserved. <b>CONFIDENTIAL</b>		
								552 Acton Road Columbus OH 43214		

- Notes:
- All locating is to be done from the two tooling holes.  
  
(Note that the tooling holes on the Top Cover line up with the tooling holes on the Probe Plate)
  - Take care to drill from the top side of the Top Cover.  
The spring holes are closest to the top of the Top Cover.



Top View  
Spring holes are closest to top side  
(See Note 2)

FINISH	MATERIAL	DEFAULT DIMENSIONS	REVISION HISTORY				Automatiq	Measurement Systems	552 Acton Road Columbus OH 43214	
Leave protective cover on	0.500" Thick Clear Polycarbonate Sheet	INCHES	REV	ECO	CHANGE	DATE				BY
		A	-	Original Drawing	21 Jun 2018	BJB				
Protect from scratches	0.125" x 0.875"	DEFAULT TOLERANCES	B	-	Update Formatting	03 Jan 2021				BJB
		C								
Break sharp corners	Stainless Steel Dowel Pin (Two)	0.000 ±0.010	D							
		0.00 ±0.025	E							
		0.0 ±0.050	F							
			G							
			H							
Versi-Traq Test Fixture							Design Study			
FMP00028.02							Top Cover – Deep and Extra Wide			
DWG-00431							REV B-1	SHEET 6/6	SIZE B	SCALE 1:2
Copyright © 2021 Automatiq Measurement Systems LLC, All Rights Reserved. <b>CONFIDENTIAL</b>										